

OIL YELLER

Heating Oil Leak Detection System For Indoor Tanks, Filters and Burner Trays



A-004



PA-010

STANDARD FEATURES OF OIL YELLER TRAYS

- ◆ Promotes clean and safe heating oil storage.
- ◆ Designed to capture leaks from tank, filter, burner fittings or overflow situation.
- ◆ Designed to protect environment during annual filter replacement. No drips on the floor.
- ◆ Two styles of tank trays available, wide trays for new tank installations and narrow trays for retrofitting existing tanks (specs on reverse).
- ◆ We produce trays for every tank type. See our product selection guide at www.oilyeller.com for your application.
- ◆ L-Shape Burner Tray (PA-005) fits under burner and around furnace or boiler and simply slides in place.
- ◆ Embossed contour design for quick alarm trigger.
- ◆ Meets requirement of CSA B139-19 clause 4.11.3, 8.2.2 and 8.2.3.



PA-002/PA-004




PA-007

LEAK DETECTION ALARM FEATURES

- ◆ Two patented alarm models to choose from: A-003 (9V battery powered) or A-004 (security system hard wire).
 - ◆ Provides leak detection pulsating 85 dB alarm every 10 seconds.
 - ◆ Velcro mounted for easy installation.
 - ◆ Typical 9V alkaline battery performance ~ 3 years.
 - ◆ Low battery warning alarm.
 - ◆ Reliable spring loaded float design.
 - ◆ Standard connections provided for security systems, allowing for 24 hour external monitoring of your entire oil system (Model A-004 alarm).
 - ◆ US Patent #6,414,598 / CDN Patent # 2,292,901. Test Standard No. 205. ANSI/UL Std. # 464 (alarming appliance).
 - ◆ Five year warranty on trays and alarms.
 - ◆ Recommended protection by Insurers and Fire Marshals.



PA-008



PA-005



PA-009



PA-001/PA-003



Vistastar Distributors
Toll Free: 1-866-OIL-LEAK
(1-866-645-5325)
Direct: 1-902-462-2643
Fax: 1-902-462-1384
Email: sales@oilyeller.com


WEB SITE:
www.oilyeller.com

PRODUCT SPECIFICATIONS



EB-002 EXTENSION BRACKET

Allows a PA-002 tray to be extended to fit beneath a standard 1136 L steel tank.



BP-002 INSTALL KIT

Required for PA-001, PA-003 and PA-009 installation when installing steel tanks with nipple legs. (Not required for fiberglass tanks)



PA-005 L-SHAPED BURNER & FILTER TRAY

DIMENSIONS (L x W x H):
31" x 31" x 2 3/4"

QTY TO TRIGGER ALARM:
1.5 L

CONTAINMENT CAPACITY:
22 L



PA-008 RECTANGULAR BURNER & FILTER TRAY

DIMENSIONS (L x W x H):
24" x 13" x 2 3/4"

QTY TO TRIGGER ALARM:
1.0 L

CONTAINMENT CAPACITY:
10.75 L



PA-001/PA-003 WIDE TRAY

DIMENSIONS (L x W x H):
72" x 27" x 5" (PA-001)
84" x 30" x 5" (PA-003)

QTY TO TRIGGER ALARM:
7.5 L (PA-001)
10.0 L (PA-003)

CONTAINMENT CAPACITY:
189 L (PA-001)
234 L (PA-003)



PA-007 HORIZONTAL TANK TRAY

DIMENSIONS (L x W x H):
49 7/8" x 70" x 3 7/16"

CONTAINMENT CAPACITY:
189 L



PA-002/PA-004 NARROW TRAY

DIMENSIONS (L x W x H):
72" x 14 1/2" x 2 3/4" (PA-002)
72" x 17 1/4" x 2 3/4" (PA-004)

QTY TO TRIGGER ALARM:
2.0 L (Both)

CONTAINMENT CAPACITY:
30 L (PA-002)
49 L (PA-004)



A-003 (9V BATTERY)/ A-004 (HARD-WIRED) LEAK DETECTION ALARM

DIMENSIONS (L x W x H):
4 1/2" x 2 3/4" x 1 1/4"

CAN/CSA—C22.2 No. 205
Signal Equipment

ANSI/UL—Std. No. 464
Audible Signal Appliance



PA-009 LARGE RECTANGULAR TRAY

DIMENSIONS (L x W x H):
52" x 34 7/16" x 3"

CONTAINMENT CAPACITY:
72 L



PA-010 SQUARE TRAY

DIMENSIONS (L x W x H):
35 1/4" x 35 1/4" x 3"

CONTAINMENT CAPACITY:
47.9 L

PRODUCT APPLICATION GUIDE:

We have a product for every tank. To view the Product Selection Guide visit our website: www.oilyeller.com