


OIL YELLER

Heating Oil Leak Detection System For Indoor Tanks, Filters and Burner Trays

STANDARD FEATURES OF OIL YELLER TRAYS

- ◆ Promotes clean and safe heating oil storage.
- ◆ Designed to capture leaks from tank, filter, burner fittings or overflow situation.
- ◆ Designed to protect environment during annual filter replacement. No drips on the floor.
- ◆ Material: oil resistant high density polyethylene.
- ◆ Two styles of tank trays available, wide trays for new tank installations and narrow trays for retrofitting existing tanks (specs on reverse).
- ◆ We produce trays for every tank type. See our product selection guide at www.oilyeller.com for your application.
- ◆ L-Shape Burner & Filter Tray (PA-005) fits under burner and around furnace or boiler and simply slides in place.



A-004



PA-010



PA-002/PA-004



PA-007

- ◆ Embossed contour design for quick alarm trigger.
- ◆ Prevents common leaks and spills from damaging the home or business environment.

LEAK DETECTION ALARM FEATURES

- ◆ Two patented alarm models to choose from: A-003 (9V battery powered) or A-004 (security system hard wire).
- ◆ Provides leak detection alarming, pulsating 85 dB alarm every 10 seconds.



PA-008



PA-005

- ◆ Velcro mounted for easy installation.
- ◆ Typical 9V alkaline battery performance ~ 3 years.
- ◆ Low battery warning alarm.
- ◆ Reliable spring loaded float design.
- ◆ Standard connections provided for security systems, allowing for 24 hour external monitoring of your entire oil system (Model A-004 alarm).
- ◆ US Patent #6,414,598 / CDN Patent # 2,292,901. Test Standard No. 205. ANSI/UL Std. # 464 (alarming appliance).
- ◆ Five year warranty on trays and alarms.
- ◆ Recommended protection by Insurers and Fire Marshals.



PA-009



PA-001/PA-003



Vistastar Distributors
Toll Free: 1-866-OIL-LEAK
(1-866-645-5325)
Direct: 1-902-462-2643
Fax: 1-902-462-1384
Email: sales@oilyeller.com

WEB SITE:
www.oilyeller.com

PRODUCT SPECIFICATIONS



EB-004 EXTENSION BRACKET

Allows a PA-004 tray to be extended to fit beneath a standard steel 330 US Gal tank.



BP-002 INSTALL KITS & NG-002 GASKETS

BP-002 required for PA-001, PA-003, PA-007, PA-009 and PA-010 installations when installing steel tanks with nipple legs. Pipe flange footings require only NG-002 gaskets. (Kits/gaskets not required for fiberglass tanks)



PA-005 L-SHAPED BURNER & FILTER TRAY

DIMENSIONS (L x W x H):
31" x 31" x 2 3/4"

QTY TO TRIGGER ALARM:
0.4 US Gal

CONTAINMENT CAPACITY:
5.8 US Gal



PA-008 RECTANGULAR BURNER & FILTER TRAY

DIMENSIONS (L x W x H):
24" x 13" x 2 3/4"

QTY TO TRIGGER ALARM:
0.26 US Gal

CONTAINMENT CAPACITY:
2.84 US Gal



PA-001/PA-003 WIDE TRAY

DIMENSIONS (L x W x H):
72" x 27" x 5" (PA-001)
84" x 30" x 5" (PA-003)

QTY TO TRIGGER ALARM:
2.0 US Gal (PA-001)
2.6 US Gal (PA-003)

CONTAINMENT CAPACITY:
41.5 US Gal (PA-001)
51.5 US Gal (PA-003)



PA-007 HORIZONTAL TANK TRAY

DIMENSIONS (L x W x H):
49 7/8" x 70" x 3 7/16"

CONTAINMENT CAPACITY:
41.5 US Gal



PA-002/PA-004 NARROW TRAY

DIMENSIONS (L x W x H):
72" x 14 1/2" x 2 3/4" (PA-002)
72" x 17 1/4" x 2 3/4" (PA-004)

QTY TO TRIGGER ALARM:
0.53 US Gal (Both)

CONTAINMENT CAPACITY:
7.9 US Gal (PA-002)
12.9 US Gal (PA-004)



A-003 (9V BATTERY) / A-004 (HARD-WIRED) LEAK DETECTION ALARM

DIMENSIONS (L x W x H):
4 1/2" x 2 3/4" x 1 1/4"

CAN/CSA—C22.2 No. 205
Signal Equipment

ANSI/UL—Std. No. 464
Audible Signal Appliance



PA-009 LARGE RECTANGULAR TRAY

DIMENSIONS (L x W x H):
52" x 34 7/16" x 3"

CONTAINMENT CAPACITY:
19.0 US Gal



PA-010 SQUARE TRAY

DIMENSIONS (L x W x H):
35 1/4" x 35 1/4" x 3"

CONTAINMENT CAPACITY:
12.65 US Gal

PRODUCT APPLICATION GUIDE:

We have a product for every tank. To view the Product Selection Guide visit our website: www.oilyeller.com