OIL YELLER

Heating Oil Leak Detection System For Indoor Tanks, Filters and Burner Trays

STANDARD FEATURES OF OIL YELLER TRAYS

- - A-004



PA-010

- Promotes clean and safe heating oil storage.
- Designed to capture leaks from tank, filter, burner fittings or overfill situation.
- Designed to protect environment during annual filter replacement. No drips on the floor.
- Material: oil resistant high density polyethylene.
- Two styles of tank trays available, wide trays for new tank installations and narrow trays for retrofitting existing tanks (specs on reverse).
- We produce trays for every tank type. See our product selection guide at www.oilyeller.com for your application.
- L-Shape Burner & Filter Tray (PA-005) fits under burner and around furnace or boiler and simply slides in place.




Prevents common leaks and spills from damaging the home or business environment.





- Two patented alarm models to choose from: A-003 (9V battery powered) or A-004 (security system hard wire).
- Provides leak detection alarming, pulsating 85 dB alarm every 10 seconds.
 - Velcro mounted for easy installation.
 - Typical 9V alkaline battery performance ~ 3 years.
 - Low battery warning alarm.
 - Reliable spring loaded float design.
 - Standard connections provided for security systems, allowing for 24 hour external monitoring of your entire oil system (Model A-004 alarm).



- Five year warranty on trays and alarms.
- Recommended protection by Insurers and Fire Marshals.



PA-008

PA-009

Vistastar Distributors 7 Devonshire Lane Lancaster, NY 14086 Toll Free: 1-866-OIL-LEAK (1-866-645-5325) Direct: 1-902-462-2643

Fax: 1-902-462-1384 Email: sales@oilyeller.com







PA-002/PA-004



PA-005

PRODUCT SPECIFICATIONS



EB-004 EXTENSION BRACKET

Allows a PA-004 tray to be extended to fit beneath a standard steel 330 US Gal tank.





BP-002 INSTALL KITS & NG-002 GASKETS

BP-002 required for PA-001, PA-003, PA-007, PA-009 and PA-010 installations when installing <u>steel</u> tanks with nipple legs. Pipe flange footings require only NG-002 gaskets. (Kits/gaskets not required for fiberglass tanks)



PA-005 L-SHAPED BURNER & FILTER TRAY

DIMENSIONS (L x W x H): 31" x 31" x 2 3/4"

QTY TO TRIGGER ALARM: 0.4 US Gal

CONTAINMENT CAPACITY: 5.8 US Gal



PA-008 RECTANGULAR BURNER & FILTER TRAY

DIMENSIONS (L x W x H): 24" x 13" x 2 3/4"

QTY TO TRIGGER ALARM: 0.26 US Gal

CONTAINMENT CAPACITY: 2.84 US Gal



PA-001/PA-003 WIDE TRAY

DIMENSIONS (L x W x H): 72" x 27" x 5" (PA-001) 84" x 30" x 5" (PA-003)

QTY TO TRIGGER ALARM: 2.0 US Gal (PA-001) 2.6 US Gal (PA-003)

CONTAINMENT CAPACITY: 41.5 US Gal (PA-001) 51.5 US Gal (PA-003)



PA-007 HORIZONTAL TANK TRAY

DIMENSIONS (L x W x H): 49 7/8" x 70" x 3 7/16"

CONTAINMENT CAPACITY: 41.5 US Gal



PA-002/PA-004 NARROW TRAY

DIMENSIONS (L x W x H): 72" x 14 1/2" x 2 3/4" (PA-002) 72" x 17 1/4" x 2 3/4" (PA-004)

QTY TO TRIGGER ALARM: 0.53 US Gal (Both)

CONTAINMENT CAPACITY: 7.9 US Gal (PA-002) 12.9 US Gal (PA-004)



A-003 (9V BATTERY) / A-004 (HARD-WIRED) LEAK DETECTION ALARM

DIMENSIONS (L x W x H): 4 1/2" x 2 3/4" x 1 1/4"

CAN/CSA—C22.2 No. 205 Signal Equipment

ANSI/UL—Std. No. 464 Audible Signal Appliance



PA-009 LARGE RECTANGULAR TRAY

DIMENSIONS (L x W x H): 52" x 34 7/16" x 3"

CONTAINMENT CAPACITY: 19.0 US Gal



PA-010 SQUARE TRAY

DIMENSIONS (L x W x H): 35 1/4" x 35 1/4" x 3"

CONTAINMENT CAPACITY: 12.65 US Gal

PRODUCT APPLICATION GUIDE:

We have a product for every tank. To view the Product Selection Guide visit our website: www.oilyeller.com